## WAXIE LED T8 LAMP

4ft Glass Series : UL Type-A : Plug + Play 14.5 Watt



## **Product Description**

Maxlite DirectFit T8 lamp is the ideal plug and play solution that works straight out of the box. Designed to deliver up to 2100 lumens, these energy-saving LED lamps are quick, easy and safe to install into existing linear fluorescent fixtures without any extra effort or re-wiring. MaxLite DirectFit LED T8 lamps utilize the existing T8 instant-start electronic ballasts, thus minimizing maintenance and labor costs.

## Features

- Wattage (Bare Lamp):
  14.5W 4FT, replaces
  32W fluorescent T8
- Lumens: 2,100 lumens
- Input Voltage: 120–277V, determined by fluorescent ballast
- UL Type-A, compatible with most electronic instantstart T8 ballasts
- All glass construction with aluminum end-caps

- Beam Angle: 320
- Color Rendering Index(CRI): 80
- THD<20%
- Power Factor: 0.90
- Suitable for use in dry and damp locations
- Suitable for use in totally enclosed recessed fixture
- Not for use with T12 magnetic or electronic ballasts

- Not for use with T8 magnetic or HO ballasts
- Not for use or to be wired to "mains voltage"
- Five year limited warranty
- 50,000 hour life (L70 standards)
- Products L14.5T8DF440-GA and L14.5T8DF450-GA are listed on the DLC QPL



## **WAXIE LED T8 LAMP**

4ft Glass Series : UL Type-A : Plug + Play 14.5 Watt

SPECIFICATIONS FOR I	1 4 F T O D F 4	O D*
SPELIFILATIONS FOR I	ГІД БІХІНДҮҮ.	- (¬ - P "

Item	Specification	4FT-Details				
General Performance	Base Lamp Wattage (W)	14.5W				
	Lumens Delivered* (lm)	2100				
	Color Temperature (CCT)	4000K 5000K				
	CRI	80				
	Beam Angle	320				
	Lumen Maintenance (L70)	50,000 hours				
Electrical	Power Factor	0.90				
Lieunida	Input Voltage	120-277V, ballast dependent				
	Operating Temperatures	-4F to 104F				
Physical	Lens	Opal (Frosted)				
	Dimension (WxMOL)	1.05"x47.78"				
Certification	Certification	DLC 4.2 Standard, cULus, RoHS				
	Material Usage	RoHS compliant, no mercury				
	Environment	Dry, Damp				
	Warranty	5 Years				

4FT T8				Average System Watts			Initial Lumens			
Item Number	MFI #	Watt	Color	Case QTY	Low BF=.78	Normal BF=.88	High BF=1.18	Low BF=.78	Normal BF=.88	High BF=1.18
555696	L14.5T8DF440-GA	14.5	4000K	25pcs	16.5	17.5	21.3	1900	2100	2350
555695	L14.5T8DF450-GA	14.5	5000K	25pcs	16.5	17.5	21.3	1900	2100	2350



